

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 1906

Revision: 26.06.2019

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: MANNOL 9966 Radiator leak-stop 325ml**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Additive
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SCT-Vertriebs GmbH  
Feldstrasse 154  
22880 WEDEL  
DEUTSCHLAND  
info@sct-germany.de
- **Further information obtainable from:** Product safety department.
- **1.4 Emergency telephone number:** Giftinformationszentrum-Nord +49-551-19240

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2 H319 Causes serious eye irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



- **Signal word** Warning
- **Hazard-determining components of labelling:**  
5-chloro-2-methyl-2H-isothiazol-3-one
- **Hazard statements**  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.
- **Precautionary statements**  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read label before use.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash thoroughly after handling.

(Contd. on page 2)



## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 1906

Revision: 26.06.2019

**Trade name: MANNOL 9966 Radiator leak-stop 325ml**

(Contd. of page 1)

- P272 Contaminated work clothing should not be allowed out of the workplace.  
 P280 Wear protective gloves / eye protection / face protection.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P321 Specific treatment (see on this label).  
 P337+P313 If eye irritation persists: Get medical advice/attention.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

- EUH208 Contains 5-chloro-2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 532-32-1 EINECS: 208-534-8	sodium benzoate Eye Irrit. 2, H319	0.5–1.5%
CAS: 10043-35-3 EINECS: 233-139-2	boric acid Repr. 1B, H360FD; Acute Tox. 4, H312	0–1%
CAS: 26172-55-4 EINECS: 247-500-7	5-chloro-2-methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	0–0.13%

- **Not dangerous substances**

CAS: 8061-51-6 EC number: 617-124-1	Lignosulfonic acid, sodium salt Eye Irrit. 2, H319	0.5–1.5%
CAS: 557-04-0 EINECS: 209-150-3	magnesium stearate	0–0.5%
CAS: 11138-66-2 EINECS: 234-394-2	Xanthan gum Skin Irrit. 2, H315; Eye Irrit. 2, H319	0.1–0.4%
CAS: 12597-70-5 EC number: 603-110-2	Bronze	0–0.25%
CAS: 7732-18-5 EINECS: 231-791-2	water, distilled, conductivity 2 or of similar purity	85–95%

- **SVHC**

10043-35-3	boric acid
------------	------------

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 1906

Revision: 26.06.2019

**Trade name: MANNOL 9966 Radiator leak-stop 325ml**

(Contd. of page 2)

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO2. Do not use water.  
Use fire extinguishing methods suitable to surrounding conditions.  
Foam  
Fire-extinguishing powder  
Sand
- **For safety reasons unsuitable extinguishing agents:** Water
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information**  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Particular danger of slipping on leaked/spilled product.  
Wear protective clothing.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

GB

(Contd. on page 4)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 1906

Revision: 26.06.2019

Trade name: MANNOL 9966 Radiator leak-stop 325ml

(Contd. of page 3)

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 1906

Revision: 26.06.2019

Trade name: MANNOL 9966 Radiator leak-stop 325ml

(Contd. of page 4)

## · Eye protection:



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

## · 9.1 Information on basic physical and chemical properties

## · General Information

## · Appearance:

Form:	Liquid
Colour:	Clear
Odour:	Characteristic
Odour threshold:	Not determined.

· pH-value: Not determined.

## · Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	100 °C

· Flash point: Not applicable.

· Flammability (solid, gas): Not applicable.

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

## · Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapour pressure at 20 °C: 23 hPa

Density at 20 °C:	0.8 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.

## · Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

## · Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

## · Solvent content:

Water:	85–95 %
VOC (EC)	0.00 %

Solids content: 4.7–15 %

(Contd. on page 6)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 1906

Revision: 26.06.2019

**Trade name: MANNOL 9966 Radiator leak-stop 325ml**

(Contd. of page 5)

**9.2 Other information**

No further relevant information available.

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
Carbon monoxide  
Aldehyde  
Poisonous gases/vapours  
Carbon dioxide

**SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:****10043-35-3 boric acid**

Oral	LD50	2,660 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

**26172-55-4 5-chloro-2-methyl-2H-isothiazol-3-one**

Oral	LD50	457 mg/kg (rat)
Dermal	LD50	660 mg/kg (rat)
	LC50/4 days	2.76 mg/L (Fish)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

GB

(Contd. on page 7)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 1906

Revision: 26.06.2019

**Trade name: MANNOL 9966 Radiator leak-stop 325ml**

(Contd. of page 6)

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity:

**26172-55-4 5-chloro-2-methyl-2H-isothiazol-3-one**

EC50 3.49 mg/kg (daphnia)

**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.

#### Additional ecological information:

##### General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### European waste catalogue

HP 10 Toxic for reproduction

#### Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

### 14.1 UN-Number

**ADR, IMDG, IATA**

UN1760

### 14.2 UN proper shipping name

**ADR**

1760 CORROSIVE LIQUID, N.O.S. (5-chloro-2-methyl-2H-isothiazol-3-one)

**IMDG, IATA**

CORROSIVE LIQUID, N.O.S. (5-chloro-2-methyl-2H-isothiazol-3-one)

(Contd. on page 8)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 1906

Revision: 26.06.2019

Trade name: MANNOL 9966 Radiator leak-stop 325ml

(Contd. of page 7)

- **14.3 Transport hazard class(es)**

- ADR, IMDG, IATA



- **Class** 8 Corrosive substances.
- **Label** 8

- **14.4 Packing group**

- ADR, IMDG, IATA III

- **14.5 Environmental hazards:**

Not applicable.

- **14.6 Special precautions for user**

Warning: Corrosive substances.

- **Danger code (Kemler):**

80

- **EMS Number:**

F-A,S-B

- **Stowage Category**

A

- **Stowage Code**

SW2 Clear of living quarters.

- **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

- **Transport/Additional information:**

- **ADR**

- **Limited quantities (LQ)**

5L

- **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

- **Transport category**

3

- **Tunnel restriction code**

E

- **IMDG**

- **Limited quantities (LQ)**

5L

- **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

- **UN "Model Regulation":**

UN 1760 CORROSIVE LIQUID, N.O.S. (5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE), 8, III

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

(Contd. on page 9)





# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 1906

Revision: 26.06.2019

**Trade name: MANNOL 9966 Radiator leak-stop 325ml**

(Contd. of page 8)

- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57**

10043-35-3	boric acid
------------	------------

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H301 Toxic if swallowed.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H360FD May damage fertility. May damage the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

- **Department issuing SDS:** Product safety department.

- **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- Acute Tox. 3: Acute toxicity – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Repr. 1B: Reproductive toxicity – Category 1B
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

- **\* Data compared to the previous version altered.**